

Behringer UMC 22 Specs

Channels of I/O 2 Inputs / 2 Outputs

Max Sample Rate/Resolution 48 kHz / 24-Bit

Display and Indicators
2 x LED (Signal)
2 x LED (Clip)
1 x LED (+48 V)
1 x LED (Power)

Connectivity

Host Connection **1 x** USB Type-B (USB 2.0)

Analog I/O
1 x Combo XLR-1/4" TRS Mic/Line Input
1 x 1/4" TRS Hi-Z Input
2 x 1/4" TRS Monitor Output
1 x 1/4" TRS Headphone Output

Phantom Power +48 V, Selectable On/Off

Digital I/O *None*

MIDI I/O *None*

Memory Card Slot *None*

Performance

Frequency Response

Inputs, Outputs:

10 Hz to 30 kHz +0/-0.5 dB

Interface:

10 Hz to 30 kHz +0/-3 dB

Max Input Level

Mic Inputs:

+2 dBu

Line Inputs:

+22 dBu

Hi-Z Inputs:

+2 dBu

Max Output Level

0 dBu

Dynamic Range

100 dBA

Impedance

Mic Inputs:

3 Kilohms

Hi-Z Inputs:

1 Megohm

Digital Audio

Sample Rates

32 / 44.1 / 48 kHz

Latency

Zero-Latency Direct Monitoring

Compatibility

OS Compatibility

macOS 10 or Later

Windows XP or Later

Power

Power Requirements

USB Bus Power

Power Consumption

2.5 W (Maximum)

Physical

Anti-Theft Features

Kensington Security Slot

Dimensions

6.4 x 4.9 x 1.8" / 162.56 x 124.46 x 45.72 mm

Weight

1.1 lb / 0.5 kg

Packaging Info

Package Weight

1.72 lb

Box Dimensions (LxWxH)

9.8 x 6.15 x 3.45"
