

Behringer MS8000 Specs

Analog Audio Inputs

Connectors	8x XLR inputs
Impedance	1 kOhm, balanced
Maximum Input Level	30 dBu at 1 kHz
Controls	4x Link 8x Lift/Ground

Analog Audio Outputs

Connectors	Link: 8x XLR outputs, parallel to inputs Direct: 8x XLR outputs
Voltage Transformation Ratio	1:1.12
Impedance	2.7 kOhms, balanced
Maximum Output Level	38 dBu at 1 kHz

System

Frequency Response	30 Hz to 30 kHz (± 0.5 dB at +4 dBu)
--------------------	---

THD+N	0.02% at 1 kHz, input level +4 dBu
-------	------------------------------------

Signal to Noise Ratio	104 dBu
-----------------------	---------

CMRR	>80 dB, typical
------	-----------------

Insertion Loss	+8 dB at 100 kOhms -5 dB at 600 Ohms
----------------	---

Power Requirement	Passive
-------------------	---------

Dimensions & Weight

Dimensions (H x W x D)	1.7 x 19.0 x 2.6" / 44 x 483 x 65 mm
------------------------	--------------------------------------

Weight	2.4 lb / 1.1 kg
--------	-----------------

Packaging Info

Package Weight	3.2 lb
----------------	--------

Box Dimensions (LxWxH)	21 x 4.5 x 3.5"
------------------------	-----------------
