Behringer MIX800 Specs

Channels	2
Inputs	2 x 1/4" TRS (balanced) 2 x RCA coaxial (unbalanced)
Outputs	2 x RCA coaxial (unbalanced)
Input Impedance	1/4": 2 kOhms (approximately) RCA: 20 kOhms (approximately)
Maximum Input Level	1/4": -20 dBu RCA: 15 dBu
Frequency Response	System: 10 Hz to 200 kHz (+0 dB / -2 dB)
Frequency Range	Output: 20 Hz to 120 kHz (±3 dB)
Dynamic Range	System: 112 dB (20 Hz to 20 kHz)
Total Harmonic Distortion (THD)	System: 0.002% typical at 4 dBu
Crosstalk	System: -75 dB at 1 kHz
Signal-to-Noise Ratio (SNR)	Output: -104 dBu System: 97 dBu at 4 dBu, A-weighted
Digital Resolution	24-bit / 40 kHz

Metering	6-digit LED output meter LED clip indicators (channels 1 and 2)
Power Supply	External Power Supply: 9 V, 750 mA Mains Voltage: 120 VAC, 60 Hz
Power Consumption	6 W
Dimensions (W x H x D)	9.6 x 1.9 x 4.7" / 242.6 x 48.0 x 120.0 mm (approximately)
Weight	1.3 lb / 0.6 kg
Packaging Info	
Package Weight	2.14 lb

Box Dimensions (LxWxH)

15.5 x 6.7 x 4.1"