

# Behringer ULM300MIC Specs

## System

---

Wireless Transmission	Digital 2.4 GHz
Number of RF Channels	17
Included Transmitters	<b>1 x</b> Handheld
Diversity	Non-Diversity
RF Channel Scanning	Auto-Scan
Max Operating Range	200' / 61 m (Line of Sight)
Max Systems per Setup	1
Audio Codec	ADPCM
Sample Rate/Resolution	48 kHz / 24-Bit
Latency	14.5 ms (Maximum)
Dynamic Range	93 dBA
Encryption	<i>None</i>

---

## Receiver

---

Form Factor	Tabletop
-------------	----------

---

Mounting Options	Tabletop
------------------	----------

---

Number of Audio Channels	1
--------------------------	---

---

Audio I/O	<b>1 x</b> XLR 3-Pin Male Balanced Line Output <b>1 x</b> 1/4" TS Female Unbalanced Line Output
-----------	--

---

Network I/O	<i>None</i>
-------------	-------------

---

Word Clock I/O	<i>None</i>
----------------	-------------

---

Power Requirements	AC/DC Power Adapter
--------------------	---------------------

---

AC/DC Power Adapter	5 VDC (Included)
---------------------	------------------

---

Display & Indicators	LED (AF Level, Power, RF Level, Transmitter Battery Status)
----------------------	---

---

Dimensions	1.6 x 4.7 x 5.9" / 41 x 119 x 150 mm
------------	--------------------------------------

---

Weight	8.8 oz / 249 g
--------	----------------

---

## Transmitter

---

Form Factor	Handheld
-------------	----------

---

RF Output Power < 10 mW

---

Audio I/O *None*

---

Muting Mute Switch

---

Auto-Level Control No

---

Power Requirements Battery

---

Battery Type **2 x AA**

---

Approx. Battery Life 24 Hour

---

Display & Indicators LED (Battery Status, Mute, Power)

---

Dimensions 2.1 x 10.2 x 2.1" / 53 x 260 x 53 mm

---

Weight 0.7 lb / 318 g

---

## Microphone

---

Form Factor Handheld

---

Sound Field Mono

---

## General

---

# Packaging Info

---

Package Weight 1.785 lb

---

Box Dimensions (LxWxH) 12.9 x 10.05 x 2.65"

---