

# Behringer DJX-750 Specs

Number of Channels **4 x Stereo**  
**1 x Mic**

---

EQ **4 x Channel EQ:**  
Low: -32 to +12 dB at 50 Hz  
Mid: -32 to +12 dB at 1.2 kHz  
Hi: -32 to +12 dB at 10 kHz  
**1 x Mic EQ:**  
Low: ±15 dB at 80 Hz  
Mid: ±15 dB at 2.5 kHz  
Hi: ±15 dB at 12 kHz  
**1 x Kill EQ:**  
Low: -54 dB at 50 Hz  
Mid: -44 dB at 1 kHz  
Hi: -26 dB at 10 kHz

---

Built-In Effects Yes

---

Sample Rates 46.875 kHz (Digital FX)

---

Bit Depths 24-Bit (AD/DA Conversion, Sigma-Delta)

---

## Connectivity

---

Audio Inputs **2 x Stereo RCA CD/Line Input**  
**2 x Stereo RCA CD/Phono Input**  
**4 x Stereo RCA Line/Phono Input**  
**1 x Stereo RCA Return Input**  
**1 x XLR 3-Pin Mic Input**

---

Audio Outputs  
**1 x** Stereo RCA Master Output  
**1 x** Stereo RCA Booth Output  
**1 x** Stereo RCA Record Output  
**1 x** Stereo RCA Send Output  
**1 x** 1/4" TRS Headphone Output

---

USB *None*

---

## Performance

---

Frequency Response 10 Hz to 55 kHz +0/-3 dB

---

Gain/Trim Range  
**Mic Input:**  
40 dB (Balanced)  
**Phono Input:**  
40 dB (Unbalanced)  
**Line Input:**  
0 dB (Unbalanced)  
**CD Input:**  
0 dB (Unbalanced)  
**Return Input:**  
0 dB (Unbalanced)

---

Output Level  
**Master:**  
+21 dBu (Max)  
**Booth:**  
+21 dBu (Max)  
**Record:**  
0 dBu (Typical)  
**Send:**  
0 dBu (Typical)

---

Headphone Output Power 180 mW (1% THD)

---

Crosstalk  
**Line:**  
>70 dB

---

SNR

**Line:**  
>80 dB

---

THD

---

## Power

---

AC Input Power

100 to 120 VAC, 50/60 Hz ⓘ

---

Power Consumption

32 W

---

## Physical

---

Dimensions (W x D x H)

12.6 x 14.6 x 4.1" / 320.0 x 370.8 x 104.1 mm

---

Weight

8.6 lb / 3.9 kg

---

## Packaging Info

---

Package Weight

11.35 lb

---

Box Dimensions (LxWxH)

17.5 x 15.5 x 6.4"

---