

Behringer DR110DSP Specs

PA Speaker

Configuration	Active 2-Way
---------------	--------------

Enclosure Type	Loudspeaker/Floor Monitor
----------------	---------------------------

Total Power Capacity	1000 W Peak
----------------------	-------------

Amplifier Power Rating	1000 W Peak
------------------------	-------------

Amplifier Class	HF: Class-AB LF: Class-D
-----------------	---

Drivers

HF Driver	1 x 1.35" / 34.29 mm Compression Driver
-----------	--

MF Driver	<i>None</i>
-----------	-------------

LF Driver	1 x 10" / 254 mm Woofer
-----------	--------------------------------

Performance

Frequency Response	55 Hz to 19 kHz \pm 3 dB
Maximum SPL	132 dB
Coverage Angle	90° H x 60° V
Max Input Level	0 dBu
I/O Impedance	Combo XLR-1/4" Input: 20 Kilohms (Balanced) 10 Kilohms (Unbalanced) XLR Output: 200 Ohms (Balanced) 100 Ohms (Unbalanced)
Protections	AC Fuse, Open Circuit, Output Limiter, Short Circuit, Thermal

Connectivity

Audio I/O	2 x Combo XLR-1/4" TRS Balanced Input 1 x 1/8" / 3.5 mm TRS Aux Input 1 x XLR 3-Pin Output
USB	<i>None</i>
Wireless Connectivity	Bluetooth
Bluetooth	4.2
Bluetooth Profiles	A2DP 1.2

Wireless Range

49.2' / 15 m

Signal Processing

Crossover

Active

EQ

1 x LF Shelf:
±12 dB at 80 Hz
1 x MF Notch/Peak:
±12 dB at 2.5 kHz
1 x HF Shelf:
±12 dB at 12 kHz
4 x Presets (Factory)

Parametric EQ

None

Semi-Parametric EQ

Yes

Filters

High-Pass:
80 Hz
100 Hz
120 Hz
150 Hz

Alignment Delay

Yes

Digital Signal Processing

Delay, Voicing Modes

Power

AC Input Power

110 VAC, 60 Hz (T 3.15 A L 250 V)

AC Power Connector

1 x IEC

Power Consumption

75 W (1/8 Power)

Physical

Mounting

1.38" / 35 mm Pole Socket

Handles

1 x Top
1 x Each Side

Cooling

Fan

Dimensions

20.5 x 12.3 x 11.9" / 520.7 x 312.4 x 302.3 mm

Weight

29.3 lb / 13.3 kg

Packaging Info

Package Weight

33.45 lb

Box Dimensions (LxWxH)

23.5 x 15 x 14.5"
