

# Behringer Feedback Destroyer Specs

Filter Type	Notch or parametric
Frequency Bands	Up to 20 per channel
Bandwidth	<i>Notch:</i> 1/60th octave <i>Parametric:</i> 1/60th octave thru 10 octaves
Number of Channels	2
Inputs	2 x XLR 2 x 1/4" TRS phone 1 x 5-pin DIN MIDI
Outputs	2 x XLR 2 x 1/4" TRS phone 2 x 5-pin DIN MIDI (out and thru)
Maximum Input Level	+20dBu @ +4dBu nominal level +6dBV @ -10dBV nominal level
Maximum Output Level	+20dBu @ +4dBu nominal level +6dBV @ -10dBV nominal level
Frequency Response	10Hz to 44kHz
Dynamic Range	107dB
Noise	<i>Not specified by manufacturer</i>

## Power Supply

Mains Voltage: 100 - 240 V, 50 - 60 Hz  
Power Consumption: approx. 10 W  
Fuse: T 1 A H 250 V

---

## Dimensions (WxDxH)

19" x 7 1/2" x 1 3/4"

---

## Weight

4.2 lbs

---

## Specialties

Extensive remote MIDI control

---

## Packaging Info

---

## Package Weight

6.25 lb

---

## Box Dimensions (LxWxH)

20.9 x 12.1 x 4.3"

---