

Behringer Europower Specs

Amplifier

Maximum Output Power	250 W + 250 W
----------------------	---------------

Limiter	Optical
---------	---------

Microphone Inputs

Type	Channels 1-4: 4 x XLR, balanced
------	---------------------------------

Sensitivity	-54 dBV
-------------	---------

Impedance	2.2 kOhms
-----------	-----------

Line Inputs

Type	Channels 1-4: 4 x 1/4" / 6.35 mm TRS, balanced
------	--

Sensitivity	-11 dBV
-------------	---------

Impedance	10 kOhms
-----------	----------

Stereo Inputs

Type	Channel 5-6: 2 x 1/4" / 6.35 mm TRS, balanced
------	---

Sensitivity	-11 dBV
-------------	---------

Impedance	10 kOhms
-----------	----------

RCA Inputs

Sensitivity	RCA Inputs (Ch 5-6): -11 dBV RCA Inputs (Ch 7-8): -11 dBV
-------------	--

Impedance	RCA Inputs (Ch 5-6): 10 kOhms RCA Inputs (Ch 7-8): 15 kOhms
-----------	--

MP3 Playback

Type	USB, type-A
------	-------------

File System	Fat 16, Fat 32
-------------	----------------

Format	MP3
--------	-----

Bit Rates	8 - 320 kbps, VBR
-----------	-------------------

Sample Rates	8, 11.025, 12, 16, 22.05, 24, 32, 44.1, and 48 kHz
--------------	--

Wireless System

USB Receiver

Behringer ULM Series USB Receiver: USB socket accepts signals from up to 2 independent Behringer ULB USB microphones

Audio Output

Type 1/4" TS, unbalanced

Impedance 1 kOhm

Level Control

Input Trim $-\infty$ to +16.5 dB

Maximum Input Level +26 dBu

Equalizer

Type Low: +/-15 dB @ 80 Hz
High: +/-15 dB @ 10 kHz

Power Supply

Mains 100 to 120 VAC 50/60 Hz (for US, JP, CA)

Power Consumption 90 W max

Connection

Standard IEC receptacle

General

Dimensions (HxWxD)

4.3 x 11.4 x 6.3" / 109.2 x 289.6 x 160.0 mm

Weight

6.6 lb / 3.0 kg

Packaging Info

Package Weight

8 lb

Box Dimensions (LxWxH)

15 x 8.5 x 6.5"
