

Behringer MS-20 Specs

Low Frequency Driver	3.6" woofer
Mid Frequency Driver	No
High Frequency Driver	2.5" Dome Tweeter
LF Amplifier	2 x 10 Watts
HF Amplifier	Not Applicable, Not Biampified
Crossover	Yes, Active
Frequency Range	65 Hz - 25 kHz
Impedance	20 kOhms
Maximum Sound Pressure Level (SPL)	<i>Not Specified by Manufacturer</i>
Controls and Indicators	1 x Power Switch 2 x Rotary Bass/Treble Control Knobs 1 x Line 1/Digital Volume Control Knob 1 x Line 2 Volume Control Knob
Connectors	2 x RCA Phono Line 2 In 1 x 1/8" Stereo Mini Line 1 In 1 x TOSLINK Optical Digital In 1 x Coaxial SPDIF Digital In

1 x RCA To Left Speaker Out
1 x 1/4: Stereo Headphone Out

Shielded Yes

Dimensions (HxWxD) 9.4 x 6.0 x 7.4" (239 x 154 x 187mm)

Weight Right Speaker: 8.1 lb (3.7 kg)
Left Speaker: 4.5 lb (2.05 kg)

Specialties Optical and SPDIF Digital Inputs
24-bit/192kHz Resolution for Digital Inputs
Ported Cabinet Front for Improved LF Response
Bass and Treble Controls
Headphone Output

Packaging Info

Package Weight 15.8 lb

Box Dimensions (LxWxH) 21 x 11.5 x 9.5"
