

Behringer F1220D Specs

PA Speaker

Configuration Active 2-Way

Total Power Capacity 250 W Peak

Amplifier Class Class-D

Drivers

HF Driver **1 x 3" / 76.2 mm Tweeter**

LF Driver **1 x 12" / 305 mm Woofer**

Performance

Frequency Range 45 Hz to 18 kHz

Input Sensitivity **Mic Input:**
-18 dBu to -37 dBu
Line Input:
+16 dBu to -4 dBu ⓘ

I/O Impedance **Mic Input:**
1 Kilohms (Balanced)
2 Kilohms (Unbalanced)

Line Input:

10 Kiloohms (Balanced)

20 Kiloohms (Unbalanced)

Output:

100 Ohms (Unbalanced)

Connectivity

Audio I/O

1 x XLR 3-Pin Balanced Line Input**1 x** XLR 3-Pin Balanced Mic Input**1 x** XLR 3-Pin Output

Signal Processing

Crossover

2 kHz (Active)

EQ

HF Shelf:

±15 dB at 12 kHz

LF Shelf:

±15 dB at 80 Hz

MF Notch/Peak:

±15 dB at 2.5 kHz

Semi-Parametric EQ

-15 dB at 350 Hz to 6 kHz, Q: 20[Ⓢ]

Dynamic Processing

Limiter

Power

AC Power Connector

1 x IEC

Power Consumption

35 W (1/8 Power)

Physical

Mounting

1 x 1.18" / 30 mm Pole Socket (Dual Angle)

Construction Material

Perforated Metal Grille, Wood

Dimensions

9.4 x 19.7 x 11.9" / 238 x 500 x 354 mm

Weight

23.6 lb / 10.7 kg

Packaging Info

Package Weight

30.3 lb

Box Dimensions (LxWxH)

23.2 x 17.15 x 12.15"
