

Behringer LC2412V2 Specs

Channels	26 (24 + 2 Switchable Channels)
DMX Interface	78 Out of 512 DMX Channels (Maximum 3 x DMX per Console-Channel)
Memory	120 Maximum Locations Chases: Maximum 99 Steps: Maximum 650, up to 99 per Chase
Connections	<p>Inputs</p> <p>Analog In: 1/4" / 6.35 mm TS Mono Jack Connector, Unbalanced Level: Line Level Footswitch: 1/4" / 6.35 mm TS Mono Jack Connector MIDI In: DIN 5-Pin Connector</p> <p>Outputs</p> <p>DMX512 Out: XLR 5-Pin Connector, Conforms to the DMX512/1990 Standard MIDI Out: DIN 5-Pin Connector Analog Out: Sub D Connector, 15-Pin Level: 0/+10 VDC Minimum Load Impedance: 600 Ohms</p>
Power	USA / Canada: 120 VAC, 60 Hz Consumption: 37 W Fuse: 100-120 VAC: T 1 A H 250 V Standard IEC Receptacle
Dimensions (HxWxD)	4.2 x 17.4 x 10.9" / 106.0 x 442.0 x 278.0 mm
Weight	8.4 lb / 3.8 kg

Packaging Info

Package Weight 10.7 lb

Box Dimensions (LxWxH) 20 x 13 x 6"
