

Behringer B207MP3 Specs

Portable PA System

Amplifier Power Rating 150 W (at 6 Ohms)

Amplifier Class Class-D

Speakers

Full-Range Driver 6.5" / 16.5 cm

Signal Processing

EQ **HF Shelf:**
±15 dB at 12 kHz
MF Notch/Peak:
±15 dB at 2.5 kHz
LF Notch/Peak:
±15 dB at 100 Hz

Dynamic Processing Optical Limiter

Performance

Frequency Response 60 Hz to 18 kHz -10 dB
90 Hz to 12 kHz -3 dB

Maximum SPL	116 dB SPL
-------------	------------

Input Sensitivity	1/4" / XLR Input: +4 to -40 dBu RCA Input: +4 to -10 dBu
-------------------	---

Gain Range	Up to +30 dB
------------	--------------

Max Input Level	+22 dBu
-----------------	---------

I/O Impedance	Hi-Z Input: 1 Megohms Line Input: 20 Kilohms RCA Input: 10 Kilohms XLR Input: 20 Kilohms
---------------	---

Connectivity

Audio I/O	3 x Combo XLR-1/4" TRS Input 1 x Stereo RCA Input XLR 3-Pin Mic/Line Thru Combo XLR-1/4" TRS Input
-----------	---

Phantom Power	+48 V (Switchable)
---------------	--------------------

USB	USB Type-A (Media Playback)
-----	-----------------------------

Media & File Formats Supported	MP3
--------------------------------	-----

Power

AC Input Power	120 VAC, 60 Hz (T 3.15 A H 250 V) 220 to 240 VAC, 50 / 60 Hz (T 3.15 A H 250 V)
----------------	--

Power Consumption	180 W (Max)
-------------------	-------------

AC Power Connector	IEC
--------------------	-----

Physical

Dimensions	10 x 14 x 8.6" / 25.4 x 35.6 x 21.8 cm
------------	--

Weight	11.2 lb / 5.1 kg
--------	------------------

Packaging Info

Package Weight	14.2 lb
----------------	---------

Box Dimensions (LxWxH)	16.3 x 12.5 x 10.9"
------------------------	---------------------
