

Behringer B115W Specs

Portable PA System

Amplifier Power Rating	LF: 700 W HF: 300 W
------------------------	--

Signal Processing

Crossover	2.2 kHz
-----------	---------

EQ	HF Shelf: ±15 dB at 12 kHz LF Shelf: ±15 dB at 80 Hz
----	---

Dynamic Processing	Optical Limiter
--------------------	-----------------

Performance

Frequency Response	Speaker: 45 Hz to 20 kHz
--------------------	------------------------------------

Input Sensitivity	1/4" / XLR Input: -36 to 0 dBu
-------------------	--

Gain Range	Up to +36 dB
------------	--------------

Max Input Level	+18 dBu
-----------------	---------

I/O Impedance	1/4" TRS Input: 14 Kilohms (Balanced) XLR Input: 14 Kilohms (Balanced)
---------------	---

Connectivity

Audio I/O	1 x XLR 3-Pin Balanced Output 2 x Combo XLR-1/4" TRS Input
-----------	---

USB	USB Type-A ⓘ
-----	--------------

Wireless

Max Wireless Range	262.5' / 80 m (Line of Sight)
--------------------	-------------------------------

Power

AC Input Power	120 VAC, 60 Hz (T 6.3 A H 250 V) 240 VAC, 50 Hz (T 3.15 A H 250 V) 230 VAC, 50 Hz (T 3.15 A H 250 V) 100 VAC, 50 / 60 Hz (T 6.3 A H 250 V)
----------------	---

Power Consumption	110 W (Max)
-------------------	-------------

AC Power Connector	IEC
--------------------	-----

Physical

Dimensions 28.1 x 16.8 x 12.3" / 713 x 427 x 313 mm

Weight 38.9 lb / 17.7 kg

Packaging Info

Package Weight 45 lb

Box Dimensions (LxWxH) 33 x 20.25 x 16"
