

Behringer UMC404HD Specs

Channels of I/O 4 Inputs / 4 Outputs

Max Sample Rate/Resolution 192 kHz / 24-Bit

Display and Indicators
4 x LED (Signal)
4 x LED (Clip)
1 x LED (+48 V)
1 x LED (Power)
2 x LED (MIDI)

Connectivity

Host Connection **1 x** USB Type-B (USB 2.0)

Analog I/O
4 x 1/4" TRS Insert Input
4 x Combo XLR-1/4" TRS Mic/Line/Hi-Z Input
2 x XLR 3-Pin Monitor Output
4 x 1/4" TRS Line Output
2 x 1/4" TRS Monitor Output
2 x Stereo RCA Line Output
1 x 1/4" TRS Headphone Output

Phantom Power +48 V, Selectable On/Off (Applied to All Inputs)

Digital I/O *None*

MIDI I/O
1 x DIN 5-Pin Input
1 x DIN 5-Pin Output

Memory Card Slot

None

Performance

Frequency Response

Mic/Line/Hi-Z Inputs:
10 Hz to 50 kHz +0/-3 dB
Interface, Outputs:
10 Hz to 43 kHz +0.3 dB

Max Input Level

Mic Inputs:
-4 dBu
Line Inputs:
+20 dBu
Hi-Z Inputs:
-3 dBu
Insert Inputs:
+3 dBu

Max Output Level

+3 dBu

Dynamic Range

100 dBA

Impedance

Mic Inputs:
3 Kilohms
Hi-Z Inputs:
1 Megohm
Insert Send:
100 Ohms
Insert Return:
10 Kilohms

Digital Audio

Sample Rates

44.1 / 48 / 88.2 / 96 / 176.4 / 192 kHz

Bit Depths	24-Bit
------------	--------

Latency	Zero-Latency Direct Monitoring
---------	--------------------------------

Compatibility

OS Compatibility	macOS 10 or Later Windows XP or Later
------------------	--

Power

Power Requirements	AC/DC Power Adapter (Included) or USB Bus Power
--------------------	---

AC Input Power	100 to 240 VAC, 50/60 Hz
----------------	--------------------------

AC/DC Power Adapter	5 VDC at 1000 mA (Included)
---------------------	-----------------------------

Power Consumption	2.5 W (Maximum)
-------------------	-----------------

Physical

Anti-Theft Features	Kensington Security Slot
---------------------	--------------------------

Dimensions	11.5 x 5.1 x 1.78" / 292.1 x 129.54 x 45.21 mm
------------	--

Weight	2.7 lb / 1.2 kg
--------	-----------------

Packaging Info

Package Weight 3.425 lb

Box Dimensions (LxWxH) 16 x 6.05 x 3.5"
