

Behringer B1200D-PRO Specs

PA Speaker

Configuration Active Subwoofer

Total Power Capacity 500 W Peak

Drivers

LF Driver **1 x 12" / 307 mm Woofer**

Performance

Frequency Range 45 Hz to 180 Hz -10 dB

Frequency Response 60 Hz to 130 Hz ± 3 dB

Maximum SPL 122 dB

Input Sensitivity +4 dBu ⓘ

Gain Range Up to +6 dB

I/O Impedance **Input:**
12 Kilohms (Unbalanced)
24 Kilohms (Balanced)

Output:
300 Ohms (Unbalanced)
600 Ohms (Balanced)

SNR > 100 dB

Protections Open Circuit, Short Circuit, Thermal

Connectivity

Audio I/O
2 x XLR 3-Pin Balanced Input
1 x XLR 3-Pin Balanced Thru/Output
1 x XLR 3-Pin Balanced Output

Signal Processing

Semi-Parametric EQ +10 dB at 40 Hz to 90 Hz ⓘ

Filters
Low-Pass:
70 to 150 Hz, 24 dB/Octave Butterworth
High-Pass:
100 Hz, 18 dB/Octave Butterworth

Dynamic Processing Optical Limiter

Power

AC Input Power
120 VAC, 60 Hz (T 6.3 A H 250 V)
220 to 240 VAC, 50 / 60 Hz (T 3.15 A H 250 V)
100 VAC, 50 / 60 Hz (T 6.3 A H 250 V)

AC Power Connector **1 x IEC**

Power Consumption 110 W

Physical

Dimensions 17 x 14.8 x 16.7" / 432 x 375 x 423 mm

Weight 43.1 lb / 19.5 kg

Packaging Info

Package Weight 44.4 lb

Box Dimensions (LxWxH) 20.5 x 20 x 18.5"
