

Behringer P16 Specs

ADC	24-Bit, Delta-Sigma
Sample Rates	44.1 / 48 kHz
Analog Inputs	16 x 1/4" TRS Line Inputs (Balanced)
Digital Inputs	2 x TOSLINK Optical ADAT
Digital Outputs	6 x RJ45 Ultranet
Recommended Cable	Shielded Cat5e
Maximum Cable Length	246' / 75 m
Signal	16 Channels plus Bus Power for P16-M
Latency	
Digital Audio Format	8-Channel ADAT: 16-/20-/24-Bit, 44.1 / 48 kHz
Synchronization	Internal or External Clock via ADAT Input A
Input Gain	-10 dBV, 0 dBu, +4 dBu, +22 dBu (Adjustable via 4-Position Gain Switch per Channel)
Nominal Input Level	+4 dBu

Maximum Input Level	+22 dBu
Dynamic Range	92 dB Typical
Frequency Response	20 Hz to 20 kHz (+0 dB, -3 dB)
Fuse	T 1 A H 250 VAC
Power Consumption	35 W
Power Requirements	100 to 240 VAC, 50/60 Hz
Dimensions (H x W x D)	1.7 x 19.0 x 7.5" / 4.4 x 48.2 x 19.0 cm
Weight	4.6 lb / 2.1 kg

Packaging Info

Package Weight	6.65 lb
Box Dimensions (LxWxH)	20.7 x 12 x 4.3"