

# Behringer X2222USB Specs

Total # Of Inputs	22 Inputs
Mic/Line Inputs	8 x XLR Microphone Inputs 12 x 1/4" TRS Line-Level Inputs
Stereo Line Inputs	4 x 1/4" TRS Left & Right Paired Inputs
AUX Sends	3
AUX Returns	3 Stereo Returns
Inserts	8
BUS (Group) Outputs	2 Sub Groups
2 Trk Master I/O	2 x Balanced XLR Outputs 2 x 1/4" TRS Outputs
ALT I/O	2 x 1/4" TRS Sub Outputs Stereo RCA 2-Track Outputs
Monitor Outputs	2 x 1/4" TRS Control Room Outputs 1 x 1/4" Stereo Headphone Output
EQ Section	3-Band EQ with Mid Sweep on Every Channel
Solo/Mute	Mute and Solo Buttons on Every Channel

Channel Level Control	60mm Faders
Trim/Gain Control	Yes
Phantom Power	+48 V Phantom
Metering	12-Segment Stereo LED Meters Clip LEDs on Every Channel
Frequency Response	Mic Input to Main Output:
Dynamic Range	<i>Not Specified by Manufacturer</i>
Signal-to-Noise Ratio	110 dB A-weighted (0 dBu In @ +22 dB Gain)
Total Harmonic Distortion (THD)	0.005% / 0.004% A-weighted
Power Supply	<i>Not Specified by Manufacturer</i>
Dimensions	3.54 x 16.93 x 14" (90 x 430 x 355 mm)
Weight	10.5 lb (4.78 kg)

## Packaging Info

---

Package Weight	14 lb
Box Dimensions (LxWxH)	20.5 x 16.6 x 6"