

Behringer VQ1500D Specs

PA Speaker

Configuration Active Subwoofer

Total Power Capacity 500 W Peak

Drivers

LF Driver **1 x 15" / 387 mm Woofer**

Performance

Frequency Range 40 Hz to 200 Hz -10 dB

Frequency Response 65 Hz to 150 Hz ± 3 dB

Maximum SPL 122 dB (Peak)

Input Sensitivity +4 dBu ⓘ

I/O Impedance **Input:**
12 Kilohms (Unbalanced)
24 Kilohms (Balanced)
Output:
300 Ohms (Unbalanced)
600 Ohms (Balanced)

SNR

Protections

Open Circuit, Short Circuit, Thermal

Connectivity

Audio I/O

2 x XLR 3-Pin Balanced Input
1 x XLR 3-Pin Balanced Thru/Output
1 x XLR 3-Pin Balanced Output

Signal Processing

Crossover

High-Pass:
100 Hz, 18 dB/Octave Butterworth

Semi-Parametric EQ

+10 dB at 40 Hz to 90 Hz ⓘ

Filters

Low-Pass:
70 to 150 Hz, 24 dB/Octave Butterworth

Phase Adjustment

0 / 180°

Power

AC Input Power

120 VAC, 60 Hz (T 6.3 A H 250 V)

Physical

Dimensions	24.3 x 19.3 x 20.8" / 616 x 490 x 528 mm
------------	--

Weight	72.8 lb / 33.1 kg
--------	-------------------

Packaging Info

Package Weight	83.45 lb
----------------	----------

Box Dimensions (LxWxH)	29 x 25.5 x 24"
------------------------	-----------------
