

Behringer DR112DSP Specs

PA Speaker

Configuration Active 2-Way

Enclosure Type Loudspeaker/Floor Monitor

Total Power Capacity 1200 W Peak

Amplifier Power Rating 1200 W Peak

Amplifier Class **HF:**
Class-AB
LF:
Class-D

Drivers

HF Driver **1 x** 1.35" / 34.29 mm Compression Driver

MF Driver *None*

LF Driver **1 x** 12" / 304.8 mm Woofer

Performance

Frequency Response	50 Hz to 19 kHz \pm 3 dB
Maximum SPL	134 dB
Coverage Angle	90° H x 60° V
Max Input Level	0 dBu
I/O Impedance	Combo XLR-1/4" Input: 20 Kilohms (Balanced) 10 Kilohms (Unbalanced) XLR Output: 200 Ohms (Balanced) 100 Ohms (Unbalanced)
Protections	AC Fuse, Open Circuit, Output Limiter, Short Circuit, Thermal

Connectivity

Audio I/O	2 x Combo XLR-1/4" TRS Balanced Input 1 x 1/8" / 3.5 mm TRS Aux Input 1 x XLR 3-Pin Output
USB	<i>None</i>
Wireless Connectivity	Bluetooth
Bluetooth	4.2
Bluetooth Profiles	A2DP 1.2

Wireless Range

49.2' / 15 m

Signal Processing

Crossover

Active

EQ

1 x LF Shelf:
±12 dB at 80 Hz
1 x MF Notch/Peak:
±12 dB at 2.5 kHz
1 x HF Shelf:
±12 dB at 12 kHz
4 x Presets (Factory)

Parametric EQ

None

Semi-Parametric EQ

Yes

Filters

High-Pass:
80 Hz
100 Hz
120 Hz
150 Hz

Alignment Delay

Yes

Digital Signal Processing

Delay, Voicing Modes

Power

AC Input Power

110 VAC, 60 Hz (T 5 A L 250 V)

AC Power Connector

1 x IEC

Power Consumption

105 W (1/8 Power)

Physical

Mounting

1.38" / 35 mm Pole Socket

Handles

1 x Top
1 x Each Side

Cooling

Fan

Dimensions

23.7 x 14.1 x 14.1" / 602 x 358.1 x 358.1 mm

Weight

37.9 lb / 17.2 kg

Packaging Info

Package Weight

43.4 lb

Box Dimensions (LxWxH)

27 x 17 x 16.25"
