

UNIFI

Dimensions	353 x 46 x 34.4 mm (13.9 x 1.81 x 1.35")
Weight	152 g (5.36 oz) with Antennas
Networking Interface	2x2 WiFi dual band / Ethernet Gigabit
Ports	(1) 10/100/1000 Ethernet
Buttons	Reset
Antennas	2 Dualband antennas
Wi-Fi Standards	802.11a/b/g/n/ac
Power Method	24V Passive PoE (Pairs 4, 5+; 7, 8 Return);802.3af Alternative A (Pairs 1, 2+; 3, 6 Return)(Supported Voltage Range: 44 to 57VDC)
Power Supply	24V, 0.5A Gigabit PoE Adapter*
Maximum Power Consumption	8.5W
Max TX Power	20 dBm
BSSID	Up to Four per Radio
Power Save	Supported
Wireless Security	WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES)
Certifications	CE, FCC, IC
Mounting	Wall/Pole/Fast-Mount (Kits Included)
Operating Temperature	-30 to 70° C (-22 to 158° F)
Operating Humidity	5 to 95% Noncondensing

ADVANCED TRAFFIC MANAGEMENT

VLAN	802.1Q
Advanced QoS	Per-User Rate Limiting
Guest Traffic Isolation	Supported
WMM	Voice, Video, Best Effort, and Background
Concurrent Clients	100+

SUPPORTED DATA RATES (MBPS)

802.11a	6, 9, 12, 18, 24, 36, 48, 54 Mbps
---------	-----------------------------------

802.11n	6.5 Mbps to 300 Mbps (MCS0 - MCS15, HT 20/40)
802.11ac	6.5 Mbps to 867 Mbps (MCS0 - MCS9 NSS1/2, VHT 20/40/80)
802.11b	1, 2, 5.5, 11 Mbps
802.11g	6, 9, 12, 18, 24, 36, 48, 54 Mbps