

Behringer PMP1680S Specs

Power Rating	1600 Watts Bridged Mono 800 Watts x2 Stereo
Mic/Line Inputs	8 Balanced Microphone: 3-pin XLR 6 Balanced Mono Line: 1/4" Phone 2 Balanced Stereo Paired Line: 1/4" Phone
Mains Inputs	1/4" Phone
In-Line Inputs>Returns	None
Aux Sends	FX Out 1 & 2: 1/4" Phone x2
Aux Returns	None
BUS (Group) Outputs	Stereo
Main Output	Main: 1/4" Phone Stereo Paired
Tape I/O	Rec: RCA Phono Stereo Paired
Monitor Outputs	Monitor: 1/4" TRS Phone
EQ Section	Channel: 3-Band EQ 7-Band Stereo Graphic
Solo/Mute	No

Channel Level Control	Rotary Pots
Trim/Gain Control	Rotary Pots
Phantom Power	+48V
Metering	5-Segment Stereo LED
Frequency Response	10Hz to 200kHz
Signal-to-Noise Ratio	110dB / 114dB A-Weighted
Total Harmonic Distortion (THD)	0.001% / 0.0007% A-Weighted
Power Supply	120V ~, 60Hz
Dimensions (HxWxD)	12.40 x 18.11 x 8.66" (315 x 460 x 220mm)
Weight	21.8lb (9.9kg)

Packaging Info

Package Weight	25.3 lb
Box Dimensions (LxWxH)	21 x 12 x 8"