

Behringer PMP6000 Specs

Power Rating	1600 Watts Bridged Mono 800 Watts Stereo x2
Mic/Line Inputs	12 Balanced Microphone: 3-pin XLR 12 Balanced Mono Line: 1/4" TRS Phone 4 Balanced Stereo Paired Line: 1/4" Phone
Aux Sends	1/4" Phone Effects Out
Inserts	12x 1/4" TRS (Mono Channels) Main Out
Main Output	Main 1 & Main 2: 1/4" TRS Phone x2 Main Rear: Stereo Speakon
Tape I/O	L/R Paired RCA Phono I/O
Monitor Outputs	Mon Send: 1/4" Phone x2
EQ Section	3-Band Channel EQ 7-Band Graphic EQ
Solo/Mute	Channel Mute / PFL
Channel Level Control	Channel Fader
Trim/Gain Control	Rotary Pots
Phantom Power	+48V

Metering	12 Segment Stereo LED
Frequency Response	10Hz to 200kHz
Signal-to-Noise Ratio	109dB / 112dB A-Weighted
Total Harmonic Distortion (THD)	0.002% / 0.0018% A-Weighted
Power Supply	120V~, 60Hz
Dimensions (HxWxD)	4.8 x 23.46 x 19.52" (122 x 596 x 496mm)
Weight	28.9lb (13.1kg)

Packaging Info

Package Weight	36.8 lb
Box Dimensions (LxWxH)	26 x 22.5 x 8"
