

Power Amplifier

Number of Channels 4

Power Rating

2 Ohms:
1600 W per Channel

4 Ohms:
860 W per Channel
2 x 3000 W Bridged

8 Ohms:
440 W per Channel
2 x 1600 W Bridged

Amplifier Class Class-D

Performance

Protections DC Fault, On/Off Muting, Reactive/Mismatched Load, Thermal

Frequency Response 20 Hz to 20 kHz +0/-2 dB

Damping Factor >145 at 8 Ohms

Input Sensitivity 0.78 V / 0 dBu

Input Impedance 10 Kilohms (Unbalanced)
20 Kilohms (Balanced)

SNR >100 dB

Distortion

Connectivity

I/O	4 x Combo XLR-1/4" Input 4 x speakON Output
-----	--

Power

AC Input Power	120 VAC, 60 Hz (T 25 A H 250 V)
----------------	---------------------------------

AC Power Connector	IEC
--------------------	-----

Power Consumption	2 Ohms: 620 W (1/8 Power)
-------------------	-------------------------------------

Physical

Display & Indicators	1 x Amber LCD (Backlit) 1 x LED (Limit, per Channel) 1 x Multi-Segment LED Meter (per Channel) 1 x Red LED (Protect, per Channel)
----------------------	--

Cooling	Fan (Variable Speed)
---------	----------------------

Dimensions	19.0 x 3.7 x 12.4" / 48.3 x 9.4 x 31.6 cm ⓘ
------------	---

Weight	13.4 lb / 6.1 kg
--------	------------------

Packaging Info

Package Weight 16.15 lb

Box Dimensions (LxWxH) 15.3 x 10 x 6.5"
