

Behringer B615D Specs

PA Speaker

Configuration	Active
---------------	--------

Total Power Capacity	1500 W
----------------------	--------

Drivers

HF Driver	1 x 1.75" / 44 mm Titanium Compression Driver
-----------	--

LF Driver	1 x 15" / 387 mm Woofer
-----------	--------------------------------

Performance

Frequency Response	50 Hz to 18 kHz
--------------------	-----------------

Maximum SPL	126 dB SPL
-------------	------------

Input Sensitivity	+4 dBu to -40 dBu
-------------------	-------------------

Max Input Level	22 dBu
-----------------	--------

Gain Range	Up to 30 dB
------------	-------------

I/O Impedance

Input:
20 Kilohms

Connectivity

Audio I/O

1 x XLR 3-Pin Mic/Line Input
1 x 1/4" TRS Input
1 x XLR 3-Pin Thru/Output

Signal Processing

Crossover

1.8 kHz

EQ

HF Shelf:
±15 dB at 12 kHz
LF Shelf:
±15 dB at 80 Hz

Dynamic Processing

Optical Limiter

Power

AC Input Power

120 VAC, 60 Hz (T 6.3 A H 250 V)

AC Power Connector

1 x IEC

Power Consumption

600 W (Max)

Physical

Dimensions 28.8 x 18.5 x 16.7" / 73.2 x 47 x 42.4 cm

Weight 57.8 lb / 26.2 kg

Packaging Info

Package Weight 64.4 lb

Box Dimensions (LxWxH) 33 x 21 x 20"
