

# EUROLIVE P1020/P1220/P1220F/P1520/P2520/P1800S

## 5. Specifications

	P1020	P1220	P1220F	P1520	P2520	P1800S
<b>SYSTEM DATA</b>						
Continuous Power (IEC268-5)	75 W	80 W	80 W	160 W	225 W	425 W
Peak Power	300 W	320 W		640 W	900 W	1700 W
Type	2-way full-range speaker					subwoofer
Frequency response	70 Hz – 20 kHz	60 Hz – 20 kHz		50 Hz – 20 kHz	45 Hz – 20 kHz	35 Hz – 250 Hz
Impedance	8 Ohm				4 Ohm	
Sound pressure level	98 dB (Full Space; 1 W @ 1 m)					98 dB (1W @ 1m)
Dispersion	90° x 40°					-
Crossover frequency	3.5 kHz				2.7 kHz	- (200 Hz recommended)
Rigging/fittings	- ergonomically shaped handles - integral tripod/stand adaptor	ergonomically shaped handle	- ergonomically shaped handles - integral tripod/stand adaptor	ergonomically shaped handles	- ergonomically shaped handles - 35-mm pole socket	
<b>COMPONENTS</b>						
HF driver	1.75" titanium-diaphragm compression driver					-
Woofers	10" (259 mm)	12" (307 mm)		15" (385 mm)	2 x 15" (385 mm)	18" (460 mm)
<b>DIMENSIONS/WEIGHT</b>						
Width	14.8 / 8.8" (375 / 223 mm)	16.5 / 10.6" (420 / 270 mm)	16.7" (424 mm)	18.1 / 12" (459 / 305 mm)	21.5" (545 mm)	26.5" (672 mm)
Height	20.3" (515 mm)	21.4" (544 mm)	21.7" (550 mm)	25.4" (645 mm)	43.6" (1108 mm)	33.5" (850 mm)
Depth	13" (330 mm)	13.1" (332 mm)	13" / 4.5" (330 / 115 mm)	13.1" (332 mm)	19.6" (497 mm)	17.6" (446 mm)
Weight	30.9 lbs (14 kg)	37.7 lbs (17.1 kg)	35.9 lbs (16.3 kg)	46.3 lbs (21 kg)	90.4 lbs (41 kg)	108.5 lbs (49.2 kg)
Shipping weight	35.3 lbs (16 kg)	41.9 lbs (19 kg)	39.7 lbs (18 kg)	48.5 lbs (22 kg)	94.8 lbs (43 kg)	116.8 lbs (53 kg)

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.