

# Behringer B15X Specs

## PA Speaker

---

Configuration	Active 2-Way
---------------	--------------

---

Total Power Capacity	1000 W
----------------------	--------

---

Amplifier Class	Class-D
-----------------	---------

---

## Drivers

---

HF Driver	<b>1 x 1"</b> / 25.4 mm Tweeter
-----------	---------------------------------

---

LF Driver	<b>1 x 15"</b> / 38.1 cm Woofer
-----------	---------------------------------

---

## Performance

---

Frequency Response	50 Hz to 20 kHz $\pm$ 3 dB
--------------------	----------------------------

---

Max Input Level	+22 dBu
-----------------	---------

---

Gain Range	-32 dB to +45 dB
------------	------------------

---

I/O Impedance	<b>XLR Input:</b> 33 Kilohms (Balanced) 16 Kilohms (Unbalanced)
---------------	---

**1/4" Input:**

33 Kilohms (Balanced)

16 Kilohms (Unbalanced)

---

## Connectivity

---

Audio I/O	<b>2 x</b> Combo XLR-1/4" TRS Balanced Input
-----------	--

---

USB	<b>1 x</b> USB Type-A (Wireless Audio)
-----	--

---

Bluetooth	4.0
-----------	-----

---

Bluetooth Profiles	GATT A2DP 1.2
--------------------	------------------

---

## Signal Processing

---

EQ	<b>LF Shelf:</b> ±10 dB at 80 Hz <b>HF Shelf:</b> ±10 dB at 12 kHz
----	---

---

## Power

---

AC Input Power	100 to 240 VAC, 50 / 60 Hz
----------------	----------------------------

---

AC Power Connector	<b>1 x</b> IEC
--------------------	----------------

---

Power Consumption	110 W (1/8 Power)
-------------------	-------------------

---

## Physical

---

Dimensions 28.1 x 16.8 x 12.3" / 712.5 x 426.7 x 312.9 mm

---

Weight 40.1 lb / 18.2 kg

---

## Packaging Info

---

Package Weight 46.55 lb

---

Box Dimensions (LxWxH) 32.5 x 21 x 16.2"

---