

Behringer B12X Specs

PA Speaker

Configuration	Active 2-Way
---------------	--------------

Total Power Capacity	1000 W
----------------------	--------

Amplifier Class	Class-D
-----------------	---------

Drivers

HF Driver	1 x 1" / 25.4 mm Tweeter
-----------	---------------------------------

LF Driver	1 x 12" / 305 mm Woofer
-----------	--------------------------------

Performance

Frequency Response	55 Hz to 16 kHz \pm 3 dB
--------------------	----------------------------

Max Input Level	+22 dBu
-----------------	---------

Gain Range	-32 dB to +45 dB
------------	------------------

I/O Impedance	XLR Input: 33 Kilohms (Balanced) 16 Kilohms (Unbalanced)
---------------	---

1/4" Input:

33 Kilohms (Balanced)

16 Kilohms (Unbalanced)

Connectivity

Audio I/O	2 x Combo XLR-1/4" TRS Balanced Input
-----------	--

USB	1 x USB Type-A (Wireless Audio)
-----	--

Bluetooth	4.0
-----------	-----

Bluetooth Profiles	GATT A2DP 1.2
--------------------	------------------

Signal Processing

EQ	LF Shelf: ±10 dB at 80 Hz HF Shelf: ±10 dB at 12 kHz
----	---

Power

AC Input Power	100 to 240 VAC, 50 / 60 Hz
----------------	----------------------------

AC Power Connector	1 x IEC
--------------------	----------------

Power Consumption	110 W (1/8 Power)
-------------------	-------------------

Physical

Dimensions 22.4 x 13.5 x 10.6" / 568 x 342 x 270 mm

Weight 28.4 lb / 12.9 kg

Packaging Info

Package Weight 32.35 lb

Box Dimensions (LxWxH) 26.5 x 17.5 x 14.4"
