

Behringer X2442USB Specs

Total # Of Inputs	24 Inputs
Mic/Line Inputs	10 x XLR Microphone Inputs 12 x 1/4" TRS Line-Level Inputs
Stereo Line Inputs	4 x 1/4" TRS Left & Right Paired Inputs
AUX Sends	4
AUX Returns	4 Stereo Returns
Inserts	8 x Channel Inserts Stereo Main Inserts
BUS (Group) Outputs	4 Sub Groups
2 Trk Master I/O	2 x Balanced XLR Outputs 2 x 1/4" TRS Outputs
ALT I/O	8 x 1/4" TRS Sub Outputs 8 x 1/4" TRS Direct Outputs Stereo RCA 2-Track Outputs
Monitor Outputs	2 x 1/4" TRS Control Room Outputs 2 x 1/4" Stereo Headphone Outputs
EQ Section	3-Band EQ with Mid Sweep on Every Channel
Solo/Mute	Mute and Solo Buttons on Every Channel

Channel Level Control	60mm Faders
Trim/Gain Control	Yes
Phantom Power	+48 V Phantom
Metering	12-Segment Stereo LED Meters Clip LEDs on Every Channel
Frequency Response	Mic Input to Main Output:
Dynamic Range	<i>Not Specified by Manufacturer</i>
Signal-to-Noise Ratio	110 dB A-weighted (0 dBu In @ +22 dB Gain)
Total Harmonic Distortion (THD)	0.005% / 0.004% A-weighted
Power Supply	<i>Not Specified by Manufacturer</i>
Dimensions	5.31 x 17.32 x 16.54" (135 x 440 x 420 mm)
Weight	13.0 lb (5.92 kg)

Packaging Info

Package Weight	17.8 lb
Box Dimensions (LxWxH)	20.4 x 20.1 x 8.3"
