

LiteBeam ac Specifications	
<b>System Information</b>	
<b>Processor Specs</b>	MIPS 74K
<b>Memory Information</b>	64 MB
<b>Networking Interface</b>	(1) 10/100/1000 Ethernet Port
<b>Physical / Electrical / Environmental</b>	
<b>Dimensions</b>	362 x 273 x 203 mm (14.25 x 10.75 x 7.99")
<b>Weight</b>	907 g (2.00 lbs)
<b>Wind Survivability</b>	200 km/h (125 mph)
<b>Wind Loading</b>	176.86 N @ 200 km/h (39.76 lbf @ 125 mph)
<b>Enclosure Characteristics</b>	Outdoor UV Stabilized Plastic
<b>Mounting Kit</b>	Pole Mounting Kit (Included)
<b>Max Power Consumption</b>	7 Watts
<b>Power Supply</b>	24V, 0.3A Gigabit PoE Adapter (Included)
<b>Power Method</b>	Passive PoE (Pairs 4, 5+; 7, 8 Return)
<b>Operating Temperature</b>	-40 to 70° C (-40 to 158° F)
<b>Operating Humidity</b>	5 to 95% Noncondensing
<b>Shock and Vibration</b>	ETSI300-019-1.4
<b>ETSI Specification</b>	EN 302 326 DN2
<b>ESD/EMP Protection</b>	± 24 KV Contact / Air
<b>Regulatory / Compliance Information</b>	
<b>Wireless Approvals</b>	FCC, IC, CE
<b>RoHS Compliance</b>	Yes