

Ubiquiti Networks AC Gen2 Specs

Power Supply	24 V, 0.3 A Gigabit PoE adapter
Power Consumption	Maximum Power Consumption 7 W
Power Method	Passive PoE (pairs 4, 5+; 7, 8 return)
Voltage	24 V \pm 10%
Operating Frequency	Worldwide 5150 - 5875 MHz USA: U-NII-1 5150 - 5250 MHz USA: U-NII-2A 5250 - 5350 MHz USA: U-NII-2C 5470 - 5725 MHz USA: U-NII-3 5725 - 5850 MHz
Gain	23 dBi
Networking Interface	1 x 10/100/1000 Ethernet port
Processor	MIPS 74Kc
Memory	64 MB DDR2
LEDs	Power, Ethernet

Channel Sizes	PtP Mode 10/20/30/40/50/60/80 MHz PtMP Mode 10/20/30/40 MHz
Enclosure	Reflector (SGCC 0.6T) Plastic: PC
Mounting	Pole-mounting kit
Wind Loading	61.8 lbf @ 125 mph (275 N @ 200 km/h)
Wind Survivability	125 mph (200 km/h)
ESD/EMP Protection	± 24 kV Contact / Air
Temperature & Humidity	Operating Temperature -40 to 158°F (-40 to 70°C) Operating Humidity 5 to 95% Non-condensing
Certifications	CE, FCC, IC
Dimensions	14.09 x 10.71 x 10.73" / 358 x 271.95 x 272.5 mm
Weight	Without Mount 1.76 lb / 0.8 g With Mount 2.16 lb / 0.9 g

Packaging Info

Package Weight	3.55 lb
----------------	---------

Box Dimensions (LxWxH)

12.2 x 6.7 x 4.9"
