

- Dimensions 196.4 x 93.5 x 32.4 mm (7.73 x 3.68 x 1.28")
- Weight 288 g (10.2 oz)
- Enclosure White Polycarbonate
- Interface Connections
 - (1) 1 Gbps SFP Port
 - (1) DC Terminal Block
 - (1) DC RJ45 Port DC Injection
 - (1) 1000 Mbps Ethernet PoE Port
- Typical Power Consumption 1.5W
- Power Method DC Terminal Block, 2-Wire, 24VDC or 50VDC
- DC In RJ45 Port, 2-Pair (4, 5+; 7, 8-) (24VDC Input), or 4-Pair (24VDC or 50VDC Input) Passthrough
- PoE RJ45 Port, 2-Pair (4, 5+; 7, 8-) (24VDC Input), or 4-Pair (24VDC or 50VDC Input) PoE Passthrough
- PoE Output PoE RJ45 Port, 2-Pair (4, 5+; 7, 8-) (24VDC), or 4-Pair (24VDC or 50VDC) PoE
- DC Output Terminal Block, 2-Wire (24VDC or 50VDC)
- Input DC Voltage 16 to 57V
- LED White: Power On Blue: Connected
- Blue (Flashing): Activity
- Operating Temperature -30 to 60° C (-22 to 140° F)
- Operating Humidity 10 to 95% Noncondensing
- ESD/EMP Protection ± 24KV Contact / Air for Ethernet
- Certifications CE, FCC, IC