

Network interface modules (NIM)

3

Maximum switched Ethernet LAN ports with PoE

48

EtherSwitch Service Module type (width)

2 single or 1 double

PoE support (wattage) without PoE boost

500 W

Intrusion prevention

Yes

Cisco Cloud Web Security

Yes

Form factor

2 RU

SSL VPN

No

Module online insertion and removal (OIR)

es

Power supply type

Internal; AC, PoE or DC

Maximum switched Ethernet ports

48

Hardware VPN acceleration (DES, 3DES, AES)

No

Redundant power supply

No

Management port

1 GE (Integrated Out of Band)

PoE support (wattage) with PoE boost

990 W

Integrated Services Card (ISC) slots

1 (PVDM 4)

Server virtualization platform (UCS E-Series)

2 core single-wide, 4 core single-wide, 4 core double-wide, 6 core double-wide, 8 core double-wide

Enhanced Services Module (SM-X)

2 single or 1 double-wide

Identity-based networking

No

Zone-based firewall and NAT services

VRF-Aware Firewall and Network Address Translation (NAT)

USB Ports (type A)

2

Integrated WAN ports

2 PoE GE / SFP; 1 GE / SFP

Default/max DRAM

4 GB / 16 GB

Default/max Flash

4 GB / 16 GB

Performance

200 Mbps upgradeable to 400 Mbps