

**Network interface modules (NIM)**

2

**Maximum switched Ethernet LAN ports with PoE**

N/A

**EtherSwitch Service Module type (width)**

N/A

**PoE support (wattage) without PoE boost**

120 W

**Intrusion prevention**

Yes

**Cisco Cloud Web Security**

Yes

**Form factor**

1 rack unit (RU), desktop

**SSL VPN**

No

**Module online insertion and removal (OIR)**

Yes

**Power supply type**

External: AC, PoE

**Maximum switched Ethernet ports**

N/A

**Hardware VPN acceleration (DES, 3DES, AES)**

No

**Redundant power supply**

No

**Management port**

1 GE (Integrated Out of Band)

**PoE support (wattage) with PoE boost**

260 W

**Integrated Services Card (ISC) slots**

1 (PVDM 4)

**Server virtualization platform (UCS E-Series)**

N/A

**Enhanced Services Module (SM-X)**

N/A

**Identity-based networking**

No

**Zone-based firewall and NAT services**

VRF-Aware Firewall and Network Address Translation (NAT)

**USB Ports (type A)**

1

**Integrated WAN ports**

1 GE / SFP 1 GE

**Default/max DRAM**

4 GB / 8 GB

**Default/max Flash**

4 GB / 8 GB

**Performance**

50 Mbps Upgradeable to 100 Mbps