

Overview

ASR1001-PWR-AC is a Cisco ASR1001 AC Power Supply, Spare.

Supported Devices

Table 1 shows the supported devices.

Model	Description
ASR1001	Cisco ASR1000-series router, QuantumFlow processor, 2.5G system bandwidth, WAN aggregation, SPA slot, SIP10, OTV, VPL, LISP
ASR1001-X	Cisco ASR1000-series router, QuantumFlow processor, 2.5G system bandwidth, WAN aggregation, SPA slot, SIP10, OTV, VPL, LISP
ASR1001-5G-VPNK9	Cisco ASR 1000 Router VPN Bundle ASR1001-5G-VPNK9
ASR1001X-5G-K9	ASR1001-X Router, 5G Base Bundle, K9, AES, Built-in 6x1G
ASR1001X-20G-K9	ASR1001-X Router, 20G Base Bundle, K9, AES, Built-in 6x1G, 2x10G
ASR1001-5G-SECK9	ASR1001-5G-SECK9 Router Security Bundle, IPsec, Firewall, AES/3DES, QuantumFlow processor, 5G system bandwidth, WAN aggregation, SPA slot, SIP10, OTV, VPL, LISP
ASR1001X-10G-K9	ASR1001-X Router, 10G Base Bundle, K9, AES, Built-in 6x1G
ASR1001X-2.5G-K9	ASR1001-X Router, 2.5G Base Bundle, K9, AES, Built-in 6x1G

Get More Information

Do you have any question about the Cisco ASR1001-PWR-AC?

Contact us now via [Live Chat](#) or sales@router-switch.com.

Specification

ASR1001-PWR-AC Specification	
General	
Device Type	Power supply - hot-plug / redundant - plug-in module
Power Device	
Input Voltage	AC 100-240 V
Input Voltage Range	AC 85 - 264 V
Frequency Required	50/60 Hz
Power Capacity	400 Watt
Compatibility Information	
Designed For	Cisco ASR 1001