

## Common

- **Conversion:** 24-bit A/D, 24-bit D/A
- **Sampling Rate:** 44.1 kHz, 48 kHz
- **Power:** USB bus powered or DC IN. When connected to an external PSU ([iRig PSU](#) **3A**, not included), iRig Stream charge the connected iOS lightning device.
- **Metering:** 3x LEDs
- **Device Connection:** mini-DIN

## Line input

- **Connector:** 2x RCA (unbal.) Left/Right
- **Nominal Input Level:** -10dBV
- **Input Impedance:** 16.5kOhms
- **Frequency Response:** 20 Hz – 20kHz

## Headset/Phones

- **Connector:** 1/8" TRRS jack (CTIA wiring standard)
- **Supply voltage:** > 2,5V
- **Microphone gain:** Adjustable with numbered thumbwheel
- **Frequency Response:** 20 Hz – 20kHz
- **Headphone Level control:** numbered thumbwheel
- **Headphone Output Power:** 100mW into 50Ohms

## Package includes

- iRig Stream interface
- Lightning to mini-DIN connection cable (60cm/23.62")
- USB C-Type to mini-DIN connection cable (60cm/23.62")
- USB A-Type to mini-DIN connection cable (60cm/23.62")

## Dimensions

- **Size:** 105.5mm/4.15" x 44.5mm/1.75" x 24mm/0.94"
- **Weight:** 65g/2.29oz