

Specifications

Minimum System Requirements

macOS: 10.8 Class Compliant

PC: Windows 7, Windows Driver

Standard USB 2.0 or USB-C Port

Mic Inputs 1-2 (balanced XLR)	
FREQUENCY RESPONSE	20 Hz – 20 kHz (+0.1 dB)
DYNAMIC RANGE	104 dB (A-weighted)
SIGNAL-TO-NOISE RATIO	104 dB (+1.0 dBu, A-weighted)
THD+N	0.002%
PREAMP EIN	-128 dBu (max gain, 150 Ω source, A-weighted)
MAX INPUT LEVEL	+1.5 dBu
GAIN RANGE	55 dB

Line Input 1-2 (balanced 1/4" [6.35 mm] TRS)	
FREQUENCY RESPONSE	20 Hz – 20 kHz (+0.05 dB)
SIGNAL-TO-NOISE RATIO	101 dB (1 kHz, +4 dBu, A-weighted)
THD+N	0.002%
MAX INPUT LEVEL	16 dBu
GAIN RANGE	55 dB

Inst Input 1-2 (unbalanced 1/4" [6.35 mm] TS)	
FREQUENCY RESPONSE	20 Hz – 20 kHz (+0.05 dB)

Inst Input 1-2 (unbalanced 1/4" [6.35 mm] TS)	
DYNAMIC RANGE	100 dB (A-weighted)
SIGNAL-TO-NOISE RATIO	98 dB (+ 4 dBu, A-weighted)
THD+N	0.005%
MAX INPUT LEVEL	6 dBu
INPUT IMPEDANCE	1 M Ω
GAIN RANGE	24 dB

Main Outputs, L and R (balanced 1/4" [6.35 mm] TRS)	
FREQUENCY RESPONSE	20 Hz – 20 kHz (+0.05 dB)
DYNAMIC RANGE / SIGNAL-TO-NOISE RATIO	106 dB (A-weighted)
THD+N	0.005%
MAX OUTPUT LEVEL	+13 dBu (1 kHz, -1 dBFS)

Headphone Output (1/4" [6.35 mm] TRS)	
THD+N	0.005%
OUTPUT IMPEDANCE	10 Ω

General	
POWER	USB-bus-powered
DIMENSIONS (WIDTH X DEPTH X HEIGHT)	8.0" x 6.0" x 2.76" (20.42 cm x 15.24 cm x 7.0 cm)
WEIGHT	2.1 lbs. 0.95 kg