

Specifications

Minimum System Requirements

- macOS: 10.8 Class Compliant
- PC: Windows 7, Windows Driver
- Standard USB 2.0 or USB-C Port

Mic Input 1 (balanced XLR)	
FREQUENCY RESPONSE	20 Hz – 20 kHz (+0.1 dB)
DYNAMIC RANGE	104 dB (A-weighted)
SIGNAL-TO-NOISE RATIO	104 dB (+1.0 dBu, A-weighted)
THD+N	0.003%
PREAMP EIN	-128 dBu (max gain, 150 Ω source, A-weighted)
MAX INPUT LEVEL	+1.5 dBu
GAIN RANGE	55 dB

Line Input 1 (balanced 1/4" [6.35 mm] TRS)	
FREQUENCY RESPONSE	20 Hz – 20 kHz (+0.05 dB)
SIGNAL-TO-NOISE RATIO	101 dB (1 kHz, +4 dBu, A-weighted)
THD+N	0.003%
MAX INPUT LEVEL	16 dBu
GAIN RANGE	55 dB

Inst Input 2 (unbalanced 1/4" [6.35 mm] TS)	
FREQUENCY RESPONSE	20 Hz – 20 kHz (+0.05 dB)

Inst Input 2 (unbalanced 1/4" [6.35 mm] TS)

DYNAMIC RANGE	100 dB (A-weighted)
SIGNAL-TO-NOISE RATIO	102 dB (+ 4 dBu, A-weighted)
THD+N	0.004%
MAX INPUT LEVEL	6 dBu
INPUT IMPEDANCE	1 M Ω
GAIN RANGE	24 dB

Main Outputs, L and R (balanced, differential 1/4" [6.35 mm] TRS)

FREQUENCY RESPONSE	20 Hz – 20 kHz (+0.06 dB)
DYNAMIC RANGE / SIGNAL-TO-NOISE RATIO	102 dB (A-weighted)
THD+N	0.005%
MAX OUTPUT LEVEL	+7 dBu (1 kHz, -1 dBFS)

Headphone Output (impedance-balanced 1/4" [6.35 mm] TRS)

THD+N	0.005%
OUTPUT IMPEDANCE	10 Ω

General

POWER	USB-bus-powered
DIMENSIONS (WIDTH X DEPTH X HEIGHT)	8.0" x 6.0" x 2.76" (20.42 cm x 15.24 cm x 7.0 cm)
WEIGHT	2.0 lbs. 0.9 kg