

## Specifications

|   |  |
|---|--|
| Channels  | 4  |
| Sensitivity   | 1.4 V                                      |
| Rated Power Output (all channels driven)                              | 125W per CH @ 4 ohms, 125W per CH @ 8 ohms |
| Signal to Noise Ratio (below rated power 20 Hz to 20 kHz, A-Weighted) | 110 dB                                     |
| THD (full rated power, 20 Hz - 20 kHz)                                | < 0.05%                                    |
| Intermodulation Distortion (from 0 dB down to -30 dB)                 | < 0.05%                                    |
| Frequency Response (at 1W, 4/8 ohms)                                  | +/- 0.5 dB                                 |
| Crosstalk (below rated power) 20 Hz to 1 kHz                          | > 70 dB                                    |
| Common Mode Rejection (20 Hz to 1 kHz)                                | > 55 dB, typically > 70 dB                 |
| Voltage Gain  | 27 dB                                      |
| DC Offset   | +/- 20mV                                   |
| Idle Power Consumption (Standard Mode)                                | 17.5W                                      |
| Dimensions  | 1.75" x 19" x 15.19"                       |
| Weight  | 10lbs/4.54kg                               |
| Shipping Weight   | 15 lbs/6.8 kg                              |
| IEC Power Connector   | 15A  |