

Crown Audio DCI4X600 Specs

Power Amplifier

Number of Channels 4

Power Rating

2 Ohms:
300 W per Channel

4 Ohms:
600 W per Channel
600 W Bridged

8 Ohms:
600 W per Channel
1200 W Bridged

16 Ohms:
300 W per Channel
1200 W Bridged

70 V / 100 V:
600 W per Channel

140 V / 200 V:
1200 W Bridged

Load Impedance / Voltage

Parallel/Stereo:
2 / 4 / 8 / 16 Ohms
70 / 100 V

Bridged/Mono:
4 / 8 / 16 Ohms
140 / 200 V

Performance

Damping Factor >1000

Input Impedance	10 Kilohms (Balanced) 5 Kilohms (Unbalanced)
-----------------	---

Max Gain	34 dB
----------	-------

SNR	>108 dB (at 8 Ohms)
-----	---------------------

THD	
-----	--

Intermodulation Distortion	$\leq 0.35\%$ ⓘ
----------------------------	-----------------

Crosstalk	>80 dB (Below Rated Power, at 1 kHz)
-----------	--------------------------------------

CMRR	>70 dB ⓘ
------	----------

Connectivity

I/O	Terminal Block 3-Pin Barrier Strip Output
-----	--

Power

AC Input Power	100 to 240 VAC, 50 / 60 Hz
----------------	----------------------------

AC Power Connector	IEC 15 A
--------------------	----------

Physical

Cooling

Fan (Variable Speed)

Dimensions

19.0 x 3.5 x 14.3" / 48.3 x 8.9 x 36.2 cm

Weight

20.1 lb / 9.1 kg

Packaging Info

Package Weight

25.5 lb

Box Dimensions (LxWxH)

22 x 20.5 x 8"
