

Crown Audio DCi 8600ND Specs

Controls	TCP/IP, network control port AVB, Ethernet port GPIO, general purpose ports
Output Power	600 W
Frequency Response	± 0.25 dB @ 8 ohms, 20 Hz - 20 kHz
Signal to Noise Ratio	AVB: > 108 dB (ref. rated power, 8 ohms, 20 Hz - 20 kHz) Analog Input: > 104 dB (ref. rated power, 8 ohms, 20 Hz - 20 kHz)
Total Harmonic Distortion	0.35% @ full rated power, 20 Hz - 20 kHz
Voltage Gain	34 dB @ maximum level setting
Damping Factor	> 1000 @ 20 Hz to 100 Hz
Input Impedance	Nominal Balanced: 10 kOhms Unbalanced: 5 kOhms
Maximum Input Level	Before Compression: +20 dBu, low gain mode
Load Impedance	Stereo/Dual Mode: 2 - 16 ohms; 70 and 100 Vrms Bridge Mono: 4 - 16 ohms; 140 and 200 Vrms
Cooling	Continuously variable speed forced air, front to back airflow

Fan Noise	47 maximum, re dBA SPL @ 1 m
-----------	------------------------------

Required AC Mains	100 - 240 V ~50/60 Hz, $\pm 10\%$
-------------------	-----------------------------------

Power Connector	20 A IEC
-----------------	----------

Dimensions	19.0 x 3.5 x 17.0" (48.3 x 8.9 x 42.5 cm)
------------	---

Weight	30 lb (13.6 kg)
--------	-----------------
