

## SPECIFICATIONS

Model Names	i8 / i8T
System type	Passive
Configuration	2-way
Frequency response (+/-3dB)	70Hz - 20kHz
Frequency range (-10dB)	50Hz - 20kHz
Sensitivity (2.83v/1m)	87dB
Calculated Maximum SPL @1m	110dB
System rated impedance	8Ω
<b>Low frequency transducer</b>	
Size	8.0"
Voice coil size	1.0"
Rated impedance	8Ω
LF Power (re:AES2-2012)	50w
<b>High frequency transducer</b>	
HF driver type	Soft dome tweeter
Voice coil size	1.0"
Diaphragm material	Silk
Rated impedance	4Ω
HF Power (re:AES2-2012)	10w
Nominal Coverage (H x V)	130° x 180°
<b>Power</b>	
System continuous power	50w
System programme power	100w
System peak power	200w
	i8T : 70v : 12.5w / 25w / 50w
	i8T : 100v : 25w / 50w
Crossover frequency	2.0kHz
Input connector	Phoenix terminals
Hardware	Wall mount brackets included
<b>Enclosure</b>	
Material and finish	Plastic (ABS)
Colour options	Black
Grille material	Aluminium
<b>Dimensions - unpacked</b>	
Height	405mm / 15.8"
Width	270mm / 10.6"
Depth	234mm / 9.2"
<b>Dimensions - packed</b>	
Height	602mm / 23.7"
Width	363mm / 14.3"
Depth	549mm / 21.6"
<b>Weight</b>	
Net weight (single speaker)	i8 : 4.7kg / 10.34lbs i8T : 5.7kg / 12.54lbs
Gross Weight (1PAIR inc brackets)	i8 : 12.7kg / 27.9lbs i8T : 14.7kg / 32.34lbs