

## SPECIFICATIONS

|                            |  |
|----------------------------|--|
| Mixing Channels            | 18 (12 Mic/Line + 2 x Stereo + 2 AUX)  |
| Inputs                     | 12 x XLR, 14 x 6.3mm Jack  |
| Outputs                    | 2 x XLR, 2 x 6.3mm Jack  |
| Headphone Output           | 6.3mm Jack   |
| FX                         | 16x Effects: (1)Hall1 (2)Hall2 (3)Room1 (4)Room2 (5)Room3(6)Platereverb1 (7)Platereverb2 (8)Platereverb3 (9)Chorus(10)Flange (11)Delay1 (12)Delay2 (13)Chorus/Room1(14)Chorus/Room2 (15)Bypass (16)Rotaryspeaker |
| EQ                         | 3 Band with HPF  |
| Phantom Power              | Yes  |
| USB                        | 16bit / 48kHz  |
| Signal To Noise Ratio      | -127dBu ±5dBu Mic Pre Equivalent Input Noise   |
| Frequency Response         | 20Hz~20kHz ±2dB  |
| Display                    | 12 Segment Level LED with power and Phantom Power indicator  |
| Dimensions:<br>(H x W x D) | 80mm x 400mm x 475mm   |
| Weight                     | 6.85kg   |