

## SPECIFICATIONS

<b>Model Name</b>	WLA-25
System Type	Passive
Configuration	Two-way
Frequency Response (+/-3dB)	108Hz - 18kHz
Frequency Range (-10dB)	108Hz - 20kHz
Sensitivity (2.83v/1m)	HF:108dB/LF:100dB
Calculated Maximum SPL @1m	HF:135dB/LF:127dB
System Rated Impedance	16Ω
<b>LF Transducer</b>	
Size	130mm / 5"
Voice-Coil Size	35mm / 1.4"
Rated Impedance	16Ω
LF Power (re:AES2-2012)	2 * 60w
<b>HF Transducer</b>	
HF Driver Type	Compression Driver
Voice-Coil Size	44mm / 1.75"
Exit size	1"
Diaphragm Material	Titanium
Rated Impedance	16Ω
HF Power (re:AES2-2012)	40w
Nominal Coverage (H x V)	100° x 10°
<b>Power</b>	
System Continuous Power	160w
System Programme Power	320w
System Peak Power	640w
Crossover frequency	3.7kHz
<b>Hardware</b>	
Input Connector	2 x speakON compatible Integral side plate adjustable rigging 0°-10°
<b>Enclosure</b>	
Enclosure Material	15mm,18mm Plywood
Finish	Rhino Black or white paint
Grille Material	1.5mm Steel
<b>Dimensions - unpacked</b>	
Height	164.5mm / 6.47"
Width	536mm / 21.10"
Depth	363mm / 14.29"
<b>Dimensions - packed</b>	
Height	235mm / 9.25"
Width	606mm / 23.85"
Depth	430mm / 16.92"
<b>Weight</b>	
Net Weight	13kg / 28.66lbs
Gross Weight	15kg / 33.06lbs