

## SPECIFICATIONS

<b>Model name</b>	EVO-X218B
System Type	Passive
Configuration	Dual 18" Subwoofer
Frequency Response (+/-3dB)	30Hz-250Hz
Frequency Range (-10dB)	28Hz-250Hz
Sensitivity (2.83v/1m)	107dB
System rated impedance	4Ω
Calculated Maximum SPL @1m	137dB
<b>Low Frequency Transducer</b>	
Size	470mm / 18" x 2
Voice coil size	76.2mm / 3"
Rated impedance	8Ω
LF Power (re:AES-2012)	2 x 600w
<b>Power</b>	
System continuous power	1200w
System programme power	2400w
System peak power	4800w
Crossover Frequency	150Hz
Input connectors	2 x NL4 (speakON Compatible) + 2 x 1/4" Jacks
<b>Hardware</b>	
Pole mount	2 x 35mm pole sockets
Handles	2 on sides
<b>Enclosure</b>	
Enclosure material	MDF
Finish	Rhino rock paint
Grille material and finish	1.2mm steel
<b>Dimensions - unpacked</b>	
Height	650mm / 25.59"
Width front	610mm / 24.02"
Width rear	610mm / 24.02"
Depth	1020mm / 40.16"
<b>Dimensions - packed</b>	
Height	765mm / 30.12"
Width front	710mm / 27.95"
Width rear	710mm / 27.95"
Depth	1120mm / 44.09"
<b>Weight</b>	
Net weight	67.3kg / 148.1lbs
Gross weight	79.9kg / 175.8lbs