

## SPECIFICATIONS

<b>Model name</b>	EVO-X215
System type	Passive
Configuration	Quasi 3-way
Frequency Response (+/-3dB)	40Hz-20kHz
Frequency Range (-10dB)	35Hz-20kHz
Sensitivity (2.83v/1m)	100dB
System rated impedance	4Ω
Calculated Maximum SPL @1m	135dB
<b>Low Frequency Transducer</b>	
Size	381mm / 15"
Voice coil size	64.26mm / 2.5"
Rated impedance	8Ω
LF Power (re:AES-2012)	2 x 350w
<b>Hi Frequency Transducer</b>	
HF Driver type	Compression driver
Voice coil size	44.5mm / 1.75"
Exit size	25mm / 1"
Diaphragm Material	Titanium
Rated impedance	8Ω
HF Power (re:AES-2012)	40w
Nominal coverage	90° x 60°
<b>Power</b>	
System continuous power	700w
System programme power	1400w
System peak power	2800w
Crossover Frequency	2.3kHz
Input connectors	2 x NL4 (speakON Compatible) + 2 x 1/4" Jacks
<b>Hardware</b>	
Pole mount	No
Handles	2 on sides
<b>Enclosure</b>	
Enclosure material	MDF
Finish	Rhino rock paint
Grille material and finish	1.2mm Steel
<b>Dimensions - unpacked</b>	
Height	1058mm / 41.65"
Width front	502mm / 19.76"
Width rear	330mm / 12.99"
Depth	467mm / 18.39"
<b>Dimensions - packed</b>	
Height	1123mm / 44.21"
Width front	564mm / 22.2"
Width rear	362mm / 14.25"
Depth	496mm / 19.53"
<b>Weight</b>	
Net weight	42.0kg / 92.4lbs
Gross weight	47.1kg / 103.61bs