

Specifications to make an IMPACT

Model Name	IMPACT-X215
System Type	Passive
Configuration	Two-way
Frequency Response (+/-3dB)	45Hz-18kHz
Frequency Range (-10dB)	40Hz-20kHz
Sensitivity (2.83v/1m)	101dB
Calculated Maximum SPL @1m	135dB
System Rated Impedance	4Ω
Low Frequency Transducer	
Size	2 x 381mm / 15"
Voice-Coil Size	65mm / 2.5"
Rated Impedance	8Ω
LF Power (re:AES2-2012)	700W
High Frequency Transducer	
HF Driver Type	Compression Driver
Voice-Coil Size	44mm / 1.75"
Exit Size	25mm / 1"
Diaphragm Material	Titanium
Rated Impedance	8Ω
HF Power (re:AES2-2012)	40W
Nominal Coverage (H x V)	90°x60°
Nominal Impedance	8Ω
Power	
System Continuous Power	700W
System Programme Power	1400W
System Peak Power	2800W
Crossover frequency	2.2kHz
Input Connector	2 x NL2 (speakON compatible) combi jack
Hardware	N/A
	2 carry handles
Enclosure	
Enclosure Material and finish	12mm MDF
Colour Options	black paint
Grille Material & Finish	1.2mm steel
Dimensions - Unpacked	
Height	1058mm / 41.7"
Width Front	444.5mm / 17.5"
Width Rear	245.3mm / 9.7"
Depth	429.0mm / 16.9"
Dimensions - Packed	
Height	1125mm / 44.3"
Width Front	520mm / 20.5"

Model Name**IMPACT-X215**

Width Rear	290mm / 11.4"
Depth	496mm / 19.5"
Weight	
Net Weight	34.5kg / 75.9lbs
Gross Weight	38.9kg / 85.6lbs