

SPECIFICATIONS

Model Name

IMPACT 215LL

System type

Passive

Configuration

2 x 15" 2-way

Frequency Response (+/-3dB)

45Hz - 18kHz

Frequency Range (-10dB)

40Hz - 20kHz

Sensitivity (2.83v/1m)

101dB

System Rated Impedance

4Ω

Calculated Maximum SPL@1m

>135dB

Low Frequency Transducer

Size

2 x 381mm / 15"

Voice coil size

65mm / 2.5"

Rated Impedance

8Ω

LF Power (re:AES-2012)

2 x 400w

HF Transducer

HF Driver type

Compression driver

Voice coil size

44mm / 1.75"

Exit size

25mm / 1"

Diaphragm Material

Titanium

Rated Impedance

8Ω

HF Power (re:AES2-2012)

40w

Nominal Coverage (HxV)

90° x 60°

Nominal Impedance

8Ω

Power

System Continuous Power

800w

System Programme Power

1400w

System Peak Power

3200w

Crossover frequency

2.2kHz

Hardware

2 x combi-jack inputs

2 x carry handles

Enclosure

Enclosure Material and finish

MDF

Colour options

Black rhino rock paint

Grille Material & Finish

Black steel

Dimensions - Unpacked

Height

1300mm / 51.18"

Width front

520mm / 20.47"

Width rear

300mm / 11.81"

Depth

500mm / 19.68"

Dimensions - Packed

Height

1367mm / 53.82"

Width front

594mm / 23.39"

Width rear

344mm / 13.54"

Depth

567mm / 22.32"

Net weight

45.0kg / 99.2lbs

Gross weight

56.0kg / 123.5lbs