

SPECIFICATIONS

System Type	Passive
Configuration	15" 2-way
Frequency Response (+/-3dB)	50Hz-20kHz
Frequency Range (- 10 dB)	40Hz-20kHz
Sensitivity (2.83v/1m)	97dB
Calculated Maximum SPL @1m	129dB
System Rated Impedance	8Ω
Low Frequency Transducer Size	381mm / 15"
Voice-Coil Size	75mm / 3.0"
Rated Impedance	8Ω
LF Power (re:AES2-2012)	400W
High Frequency Transducer HF Driver Type	Compression Driver
Voice-Coil Size	44mm / 1.75"
Exit Size	25mm / 1"
Diaphragm Material	Titanium
Rated Impedance	8Ω
HF Power (re:AES2-2012)	40W
Nominal Coverage (H x V) Power	Hybrid Symmetry Horn 100°x80°
System Continuous Power	400w
System Programme Power	800W
System Peak Power	1600w
Crossover frequency	2.7kHz
Input Connector	2 x NL4 (speakON compatible) 35mm Speaker Pole Insert with lock screw
Hardware	2 handles on sides M8 x 10 rigging points
Enclosure	
Enclosure Material	Trapezoidal / Polypropylene
Finish	Black / white
Grille Material & Finish	1.2 steel
Dimensions - Unpacked	
Height	728.5mm / 28.7"
Width Front	480.6mm / 18.9"
Width Rear	480.6mm / 18.9"
Depth	395.6mm / 15.6"
Dimensions - Packed	
Height	830mm / 32.7"
Width Front	514mm / 20.2"
Width Rear	514mm / 20.2"
Depth	489mm / 19.3"
Weight	
Net Weight	22.0kg / 48.4lbs
Gross Weight	26.8kg / 59.0lbs