

SPECIFICATIONS

Model name	EVO-X15
System Type	Passive
Configuration	2-way
Frequency Response (+/-3dB)	45Hz-20kHz
Frequency Range (-10dB)	40Hz- 20kHz
Sensitivity (2.83v/1m)	98dB
System rated impedance	8Ω
Calculated Maximum SPL @1m	130dB
Low Frequency Transducer	
Size	381mm / 15"
Voice coil size	64.26mm / 2.5"
Rated impedance	8Ω
LF Power (re:AES-2012)	350w
Hi Frequency Transducer	
HF Driver type	Compression driver
Voice coil size	44.5mm / 1.75"
Exit size	25mm / 1"
Diaphragm Material	Titanium
Rated impedance	8Ω
HF Power (re:AES-2012)	40w
Nominal coverage	90° x 60°
Power	
System continuous power	350w
System programme power	700w
System peak power	1400w
Crossover Frequency	2.2kHz
Input connectors	2 x NL4 (speakON Compatible) + 2 x 1/4" Jacks
Hardware	
Pole mount	Dual Angle (0° or 10°) 35mm Pole Socket
Handles	2 on sides
Enclosure	
Enclosure material	MDF
Finish	Rhino rock paint
Grille material and finish	1.2mm steel
Dimensions - unpacked	
Height	675mm / 26.57"
Width front	460mm / 18.11"
Width rear	294.5mm / 11.59"
Depth	450mm / 17.72"
Dimensions - packed	
Height	750mm / 29.53"
Width front	524mm / 21.02"
Width rear	324mm / 12.76"
Depth	486mm / 19.13"
Weight	
Net weight	24.7kg / 54.3lbs
Gross weight	28.4kg / 62.3lbs