

Specifications to make an IMPACT

Model Name	IMPACT-X15
System Type	Passive
Configuration	Two-way
Frequency Response (+/-3dB)	50Hz-18kHz
Frequency Range (-10dB)	45Hz-20kHz
Sensitivity (2.83v/1m)	98dB
Calculated Maximum SPL @1m	130dB
System Rated Impedance	8Ω
Low Frequency Transducer	
Size	381mm / 15"
Voice-Coil Size	65mm / 2.5"
Rated Impedance	8Ω
LF Power (re:AES2-2012)	350W
High Frequency Transducer	
HF Driver Type	Compression Driver
Voice-Coil Size	44mm / 1.75"
Exit Size	25mm / 1"
Diaphragm Material	Titanium
Rated Impedance	8Ω
HF Power (re:AES2-2012)	40W
Nominal Coverage (H x V)	90°x60°
Nominal Impedance	8Ω
Power	
System Continuous Power	350W
System Programme Power	700W
System Peak Power	1400W
Crossover frequency	2.2kHz
Input Connector	2 x NL2 (speakON compatible) combi jack
Hardware	Dual-angle (0° or 10°) 35mm pole socket 2 carry handles
Enclosure	
Enclosure Material and finish	12mm MDF
Colour Options	black paint
Grille Material & Finish	1.2mm steel
Dimensions - Unpacked	
Height	680mm / 27.1"
Width Front	443.5mm / 17.5"
Width Rear	243.5mm / 9.6"
Depth	429.0mm / 16.9"
Dimensions - Packed	
Height	750mm / 29.5"
Width Front	520mm / 20.5"

Model Name**IMPACT-X15**

Width Rear	290mm / 11.4"
Depth	485mm / 19.1"
Weight	
Net Weight	22kg / 48.4lbs
Gross Weight	26kg / 57.2lbs